



BURAQ

# THERMAL TRANSFER BARCODE PRINTER



## BT350/BT350W

- ▶ DUAL-WALL FRAME, ROBUST AND STURDY STRUCTURE
- ▶ ARM9 32-BIT PROCESSOR WITH 128 MB RAM, 256 MB FLASH MEMORY
- ▶ 300M RIBBON SUPPLY ON A 0.5"/1"/1.5" CORE
- ▶ USB, ETHERNET, SERIAL AS STANDARD, OPTIONAL PLUG AND PLAY BLUETOOTH OR WI-FI
- ▶ BUNDLE SEAGULL WINDOWS DRIVER AND BARTENDER
- ▶ ZPL, DPL, EPL, TSPL EMULATION SUPPORTED
- ▶ VARIOUS ACCESSORIES INCLUDE EXTERNAL ROLL HOLDER, PEELING MODULE, CUTTER MODULE



# SPECIFICATION



ITEM	HT800	HT830
PRINTING	PRINTING METHOD	THERMAL TRANSFER
	RESOLUTION	203DPI
	MAX. PRINTING SPEED	152MM/S
	MAX. PRINTING WIDTH	108MM
	MAX. PRINTING LENGTH	1200MM
CPU	32-BIT RISC CPU	
MEMORY	RAM	128 MB
	FLASH	256 MB
DETECTION	SENSOR OUT-OF-PAPER DETECTION, GAP DETECTION, RIBBON DETECTION, BLACK MARK DETECTION, COVER-OPENING DETECTION	
MEDIA	TYPES	BLACK MARK LABEL, PUNCHED HOLE LABEL, FOLDING OR ROLLING DIE CUTTING LABEL
	WIDTH	1" (25.4MM)-4.33" (110MM)
	HEIGHT	0.0787" (20MM)-9.84" (250MM)
	THICKNESS	0.002"(60UM)-0.01"(250UM)
	LABEL ROLL DIAMETER	5"(127 MM) MAX
	CORE DIAMETER	0.5"(12.7 MM), 1"(25.4 MM). 1.5"(38 MM)
RIBBON	TYPE	WAX, WAX/RESIN, RESIN
	WIDTH	2" (50MM)-4.38" (118MM)
	LENGTH	984'(300 M)
	CORE DIAMETER	1"(25.4 MM)
PROGRAMMING LANGUAGE	ZPL, TSPL,EPL,DPL	
SOFTWARE	LABEL DESIGN SOFTWARE	HPRT BARTENDER ULTRALITE (PROFESSIONAL AND HIGHER VERSIONS ARE AVAILABLE FOR TRIAL)
	DRIVER	WINDOWS VISTA7,8,10, SERVER 2012/2016/2018
RESIDENT FONTS	BITMAP FONTS TTF FONTS 6, 8, 12, 16, 32, OCR A & B. 90°, 180°, 270° ROTATABLE AND 10 MAGNIFICATION. CG TRIUMVIRATE™TIMES EXPANDABLE IN HORIZONTAL AND VERTICAL DIRECTIONS, SIMPLIFIED CHINESE.	
CODE PAGES	DOS437,720,737,755,775,850,852,855,856,857,858,860,862,863,864,865,866, WINDOWS 1250,1251,1252,1253,1254,1255,1256,1257,1258, ISO8859-1,-2,-3,-4,-5,-6,-8,-9,-15	
BARCODES	1D	CODE 39, CODE 93, CODE 128UCC, CODE 128 SUBSET A, B, C, CODABAR, INTERLEAVE 2 OF 5, EAN-8, EAN-13, EAN-128,UPC-A, UPC-E, EAN AND UPC 2 (5) DIGITS ADD-ON, MSI, PLESSEY, POSTNET, RSS-STACKED, GS1 DATABAR, CODE 11
	2D	PDF417, MAXICODE, DATAMATRIX, QR CODE, AZTEC
INTERFACES	STANDARD	USB, SERIAL,ETHERNET
	OPTIONAL	BLUETOOTH 4.0/BLE, WIFI
CONTROL PANEL	TWO-COLOR STATUS LIGHT: POWER INDICATOR, STATUS INDICATOR FOUR CONTROL BUTTONS: POWER BUTTON, PAUSE BUTTON, FEED BUTTON, CANCEL BUTTON	
POWER SUPPLY	POWER SWITCH INPUT: AC 100-240 V, 50/60 HZ OUTPUT: DC 24 V / 2 A	
ENVIRONMENT	OPERATION	41°F(5°C) TO 104°F(40°C) , HUMIDITY 30% TO 85% ,NON-CONDENSING
	STORAGE	-4°F(-20°C) TO 122°F(50°C), HUMIDITY 10% TO 90% ,NON-CONDENSING
PHYSICAL CHARACTERISTIC	DIMENSION(L*H*W)	308*250*180MM
	WEIGHT	2.8KG, EXCLUDING MEDIA
OPTIONS & ACCESSORY	PEELER MODULE, CUTTER MODULE, EXTERNAL LABEL ROLL HOLDER	
AGENCY APPROVAL	CCC,CE,FCC,RoHS	